
B1 AVENGER M50 - MANUAL

MANUAL SURFACE SET DROP AND SWING ARM - MODEL DACB-PAM-1200-DS


CRASH TESTED TO ASTM F2656-07 - M50/P3 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT





B1 AVENGER M50 - MANUAL MANUAL SURFACE SET DROP AND SWING ARM - MODEL DACB-PAM-1200-DS

CRASH TESTED TO ASTM F2656-07 - M50/P3 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT




1. CONCRETE PADS ARE RECOMMENDED (PROVIDED BY OTHERS)

| F | |
|--------------------|---------------|
| DROP AND SWING ARM | SHEET: 2 OF 3 |
| | 20230104-10-W |
| | SCALE: N.T.S. |

B1 AVENGER M50 - MANUAL

MANUAL SURFACE SET DROP AND SWING ARM - MODEL DACB-PAM-1200-DS

CRASH TESTED TO ASTM F2656-07 - M50/P3 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT





8015 THORNDIKE ROAD GREENSBORO, NC 27409 (336) 617-8478 www.barrier1.com sales@barrier1.com

THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE PROPRIETARY AND CONFIDENTIAL, AND ARE AUTHORIZED ONLY FOR USE FOR WORK ASSOCIATED WITH BARRIER1 SYSTEMS, LLC ALL RIGHTS RESERVED.

PLAN VIEW

NOTE

- 1. CONCRETE PADS ARE RECOMMENDED (PROVIDED BY OTHERS)
- 2. REMOVE PIN AT TOP OF MECHANICAL SPRING ASSIST TO SWING BARRIER HORIZONTALLY

3000 P.S.I. CONCRETE PAD 72" X 84" X 6" DEEP (TYP)

| | DROP AND SWING ARM | SHEET: 3 OF 3 |
|--|--------------------|---------------|
| | | 20230104-10-W |
| | | SCALE: N.T.S. |